

control cabinet for industry gas alarming detector and gas leak sensor

Xi'an Hua Fan Instrument Co.,Ltd is one of the leading 13 multi-function inspection alarm control cabinet manufacturers and suppliers in China, welcome to buy or wholesale 13 multi-function inspection alarm control cabinet made in China from us.



Basic parameters

Size : 460 mm * 300 mm * 150 mm

Weight: about 7 kg

Working voltage: AC220V 50 Hz

Output voltage: DC24V

The number of channels: 1-8

Digital tube display mode: highlight inspection way

Response time: $\leq 8s$

Signal input: 1-8 standard 4-20 mA current loop road input,

support two wire and three-wire system all sorts of transmitter

Signal output: (optional) 1-8 standard 4-20 mA current loop output,

and with input signal one to one

Control output: 1-8 public relay output, 1 road output relay ,

Relay and when any alarm all the way

Sampling accuracy: 12 bit AD

Measurement range: 0-9999 (can be set)

Alarm : first alarm more than 90 dB alarm way; second alarm more than 120 dB

Temperature range: - 10 °C ~ 50 °C

Humidity: 15% ~ 70% RH (No condensation)

System power: < 50 W (8 road with no alarm)

Execution standard: the combustible gas alarm controller GB16808-1997 technical requirements and test methods,

Installation method: wall-mounted installation